


IRON MAN

6" Half-Round Seamless Rollformer



IronMan Next Generation Smart Machine
available on all IronMan models

Use the touch screen to automatically control product length, add for miters, if applicable, and keep a total of daily material ran and total footage. Password protected.

Reverse Curl Front Hem Bar

- Unique reverse bead profile (standard single side painted coil)
- 12 forming stations; .002 hard chrome rollers

Polyurethane Drive Train

- 5 station polyurethane drive train
- Eliminates slippage from cold weather and condensation
- Rollform a broad range of materials (aluminum, copper, steel)

Hardcoat Anodized Radius Forming Rollers

- Free-floating rollers produce less pressure and more product uniformity
- Aluminum forming roller (reduces machine weight)

Structural Steel Frame

- Welded tubular frame

Modular Turnstile Upright System

- Transfer bars (ease of coil loading)

ROCK SOLID GUARANTEE: 3-YEARS Parts & Labor/Mechanical ▪ **1-YEAR Parts & Labor/Electrical**

www.kwmgutterman.com

795 South Larkin Avenue, Rockdale, Illinois 60436 ▪ **E-mail** sales@kwmgutterman.com

Phone (815) 725-9205 ▪ **Fax** (815) 725-4429 ▪ **Toll-free** (888) 729-4290





6" Half-Round Seamless Rollformer

SPECIFICATIONS

<p>Power 1 ½ HP, 110 volt, single phase, 18 ampere, totally enclosed fan cooled (T.E.F.C.) motor</p>	<p>Dimensions Length – 169" (429.26 cm) Height – 50" (127.0 cm) Width – 24" (61.0 cm)</p>													
<p>Weight Approximately 1,510 lbs. (589.7 kg)</p>	<p>Drive Powered polyurethane drive rollers via chains and sprockets</p>													
<p>Shear Front pull guillotine</p>	<p>Speed Approximately 35 feet per minute</p>													
<p>Controls Push button entry and exit end controls with "jog" feature</p>	<p>Options</p> <ul style="list-style-type: none"> ▪ Smart Machine (automated length control) ▪ Machine mount cradles ▪ Additional runout support stands ▪ CE Certified wiring ▪ Additional turnstiles ▪ Additional spools ▪ Trailer riser pad 													
<p>Recommended Materials Maximum width 11.875" (30.16 cm)</p> <table border="0"> <thead> <tr> <th>Material</th> <th>Maximum Gauge</th> </tr> </thead> <tbody> <tr> <td>Painted steel</td> <td>26</td> </tr> <tr> <td>Galvalume</td> <td>26</td> </tr> <tr> <td>Aluminized steel</td> <td>26</td> </tr> <tr> <td>Ternecoat steel</td> <td>26</td> </tr> <tr> <td>Aluminum</td> <td>.032</td> </tr> <tr> <td>Copper</td> <td>16 oz. 3/4 hard</td> </tr> </tbody> </table>		Material	Maximum Gauge	Painted steel	26	Galvalume	26	Aluminized steel	26	Ternecoat steel	26	Aluminum	.032	Copper
Material	Maximum Gauge													
Painted steel	26													
Galvalume	26													
Aluminized steel	26													
Ternecoat steel	26													
Aluminum	.032													
Copper	16 oz. 3/4 hard													

www.kwmgutterman.com

795 South Larkin Avenue ■ Rockdale, Illinois 60436 ■ **E-mail** sales@kwmgutterman.com

Phone (815) 725-9205 ■ **Fax** (815) 725-4429 ■ **Toll-free** (888) 729-4290

